

LETTER OF CERTIFICATION For STAR TRITON

June 12, 2018

To whom it may concern:

This is to certify that STAR TRITON, Premium Grade Sealcoating, manufactured by STAR Licensee plants;

- 1. <u>Does not contain coal tar or coal tar derivative.</u> It is based on a specialty petroleum resin. The Chemical Abstract Service (CAS) Number of the specialty petroleum resin is 64742-90-1, whereas for Refined Coal Tar is 65996-93-2.
- 2. The PAHs content for the recommended mix design with 35-40% water of dilution and 2-3 lb. of sand is lower than 1%; typically in the range of 0.77-0.83% by weight.
- 3. It is clay stabilized water-borne sealcoating, which is fortified with rubber polymers, and chemicals for outstanding durability and appearance.
- 4. It meets and or exceeds the requirements of the following specifications:

Property	Test Method	Specification	Status-TRITON
Penetration	ASTM D 5	Min 40 dmm	Meets
Weight/gallon	ASTM D 244	9 lb/GalMin.	Meets
Wet Track Abrasion	ASTM D 3910	39 gms./sq. ft.	Meets
Residue by Evaporation	ASTM D 2939	58% Min.	Meets
Resistance to Kerosene	ASTM D 5727	No discoloration	Meets

- 5. Shall be suitable for application with squeegee or spray, at the specified application rates.
- 6. Is considered an Industrial Waste not a hazardous waste either in wet of dry form.
- 7. Does not require special placarding during transportation.

Please contact the undersigned for additional information, if desired.

Sincerely, S.T.A.R., INC.

mish Marluy

Girish C. Dubey President E-mailgcdubey@starseal.com

QUALITY 🔺 PERFORMANCE 🔺 VALUE 🔺 INNOVATION 🔺 SERVICE

800-759-1912 www.starseal.com