



PRODUCT BULLETIN

STAR MACRO-FLEX®

(Polymeric Latex Additive for Coal Tar Sealer)

MEETS FAA-P-627,628 SPECIFICATIONS

STAR MACRO-FLEX® reinforces and adds substantial benefits to Coal Tar Sealers;



- * Faster Drying Time,
- * Longer Lasting, Increased Toughness & Flexibility,
- * Uniform charcoal black color upon drying,
- * Capacity to suspend higher amounts of aggregate (sand, etc.) in the sealer mix design,
- * Improved Gasoline, Oil and Chemical Resistance.

RECOMMENDED USES

On all asphalt surfaces, subject to moderate to heavy traffic and or frequent abuse by harsh chemicals, gasoline, oil, grease, etc...

- * Airports, Runways & Taxiways
- * Commercial and Industrial Parking Lots
- * Fast-Food Restaurants
- * Gas Stations
- * Recreational Areas
- * Residential Driveways

PROPERTIES & SPECIFICATIONS

Solid, % by Weight	40.00
Polymer Type	Acrylonitrile/butadiene
Acrylonitrile/Butadiene, ratio	30-49 / 51-70
Weight/Gallon	8.25 Lbs.

PRECAUTIONS

Keep from freezing. Observe all safety precautions. Consult Material Safety Data sheet for details.

KEEP OUT OF REACH OF CHILDREN.

PACKAGING - 5 gallon plastic pails.

SUGGESTED FORMULATIONS

Type	Sealer RP-355e	Water	Sand Lbs.	STAR Macro Flex®	Coverage Gal/Sq. Yd.
1 st & 2 nd coat	100 Gallons	30-40 Gallons	300-500	3 Gallons	.12-20

Based on total gallons of the mixture of sealer, water, aggregate and STAR MACRO-FLEX®.