

# ★ PRODUCT BULLETIN

## STAR MACRO-FAST®

Rapid Drying Additive for Seal Coatings

### GENERAL DESCRIPTION

**STAR MACRO-FAST®** is a latex additive that speeds up the drying of seal coatings Without increasing their viscosity. Based on rubberizing polymers & specialty chemicals, **STAR MACRO-FAST®** also improves the overall performance & durability of the seal coating.

### OUTSTANDING PROPERTIES



- \* Speeds up drying of seal coatings thereby reducing labor cost.
- \* Recommended for both refined coal tar and asphalt emulsion based seal coatings.
- \* Does not affect viscosity of the sealer.
- \* Hardens the seal coating and reduces power steering marks, scuffing and tearing.
- \* Makes seal coatings dry blacker and more uniformly under sun or shade.
- \* Improves tensile strength, flexibility and adhesion.
- \* Improves fuel and chemical resistance.
- \* Water (latex) based; Water clean up. Safe to use and store.

### RECOMMENDED USES

**STAR MACRO-FAST®** is recommended for all applications where faster drying is a must, e.g. Fast Food Restaurants - Service Plazas - Apartment & Office Complexes - Gas Stations

### SUGGESTED MIX DESIGNS (Shown in the order of addition)

#### MIXING PROCEDURE

Star-Seal Asphalt Pavement Sealer -ASTM 5727	100 Gallons
Water	35 - 40 Gallons
<b>MACRO--FAST®</b>	2 - 5 Gallons
Sand/Aggregate	200--500 Lbs.

#### Weather/Ambient Conditions Temperature:

50 deg. F and forecasted for the next 8 hrs.

Relative Humidity- Less than 60% is preferred, Max 80%.

Do not apply on rainy, foggy or extremely humid days.

### PRECAUTIONS

Keep from freezing. Observe all safety precautions. Consult Material Safety Data sheet for details.

**KEEP OUT OF REACH OF CHILDREN.**

PACKAGING - 5 gallon pails